

Alea entrance panel - B/W Video -



Description

Compact ALEA entrance panel with 1 push-button for hands-free B/W video dig sys (M3710V2 and M1717V2E/T). Possibility of connecting up to 16 panels of this reference for the same dwelling or block. General panel connection not available. It has a G3250 audio control group, B/W telecamera with infrared led support lighting and jumper to select the type of cable that will transmit the video signal (coaxial or UTP CAT5), 1 call push-button and its corresponding card-holder with backlit leds providing easy replacement and customization . Security external keyboard manufactured in stainless steel with watertight electronic push-button, providing greater resistance to weathering and the continuous use.Housing manufactured in 2mm width stainless steel and 5mm width smoked methacrylate, which gives greater robustness. Flush-mounted installation using fixing frame and hidden screws for a perfect fit against the wall and vandal-proof protection. Hinge mechanism for a 180° open to both sides in order to facilitate its installation and water drainage system to greatly reduce the risk of damage caused by humidity and water inlet.Flush-mounted box not included, request it separately.

Gross Price

Alea entrance panel - B/W Video - 1 push-button in 1 column

REF.	PDV401S
Sistema	DIGITAL
Product Family	PUSH BUTTONS COMPREHENSIVE-COMPACTS STREET PANEL

Technical Characteristics

Power supply: 17Vdc Consumption: Standby mode: 42,50mA Ring mode: 410,5mA Audio+video mode: 350,5mA(MIN) 525,5mA(MAX). Housing: Material: 2mm Stainless steel, 5mm Smoked methacrylate. Working temperature: from -30°C to +50°C.

Measurements: Dimensions: 150mm(H)x214,5mm(V) Flush-mounted box: 120mm(H)x189mm(V)x46mm(D)